



PVC Temp Floor Tile Specifications

| | | |
|-----------------------------|--|------------------------|
| MODULE SIZE: | WIDTH 6" LENGTH 24" THICKNESS 3/4" | 1 TILE = 1 SQUARE FOOT |
| MODULE WEIGHT: | 1.1 LBS PER TILE/PER SQUARE FOOT | |
| MATERIAL: | HIGH-IMPACT POLYPROPYLENE CO-POLYMER UV INHIBITORS ADDED. | |
| FIRE RATING: | ASTM E-648 DATA SHEET ATTACHED. EXTENT OF FLAME TRAVEL (MM) 1070 CRITICAL RADIANT FLUX (W/cm sq.) IS 0.08 | |
| SUPPORT STRUCTURE: | FLOORING MODULE INCORPORATES MULTI-DIRECTIONAL STRUCTURAL SUPPORT RIBBING, ALLOWING FOR DISTRIBUTION OF WEIGHT LOADS. | |
| WEIGHT LOADING: | 27,000 lbs/sqft | |
| GROUND SURFACES: | TEMP FLOOR'S UNIQUE HINGED DESIGN ALLOWS FOR USE ON UNEVEN SURFACES-ON GRASS,SAND GRAVEL,CONCRETE,ASPHALT ICE,SNOW ETC, WITH LITTLE SUB-SURFACE PREPARATION | |
| SHIPPING: | 40" x 48" PALLET TEMP FLOOR IS DELIVERED PRE-ASSEMBLED IN 3" x 4" PANELS [12 TILES TO A PANEL] EACH PALLET CAN BE LOADED WITH UP TO 100 PANELS [1200 TILES] OR 1200 SQ.FT. [3" x 4" x 8"] PALLET DIMENSIONS 20' OCEAN CONTAINER 12,000 sq.ft. 40' OCEAN CONTAINER 20,000 sq.ft. 48' TRUCK 24,000 sq.ft. 53' TRUCK 28,800 sq.ft | |
| FUNCTIONAL FEATURES: | <ol style="list-style-type: none">1. INDIVIDUAL MODULAR PANELS INTERCONNECT EASILY IN 12 sq.ft. SECTIONS2. TEMP FLOOR'S HINGE DESIGN ALLOWS FOR THE MODULES TO BE ROLLED-UP FOR DISASSEMBLY IF SO DESIRED. 6' x 20' ROLLS CAN BE EFFICIENTLY HANDLED.3. EACH TILE FEATURES AN ATTRACTIVE TEXTURED NON-SLIP SURFACE | |

WITH A MULTITUDE OF AERIATION HOLES FOR TEMPORARY USE ON GRASS SURFACES.

4. EACH TILE INCORPORATES A HALF-MOON NETWORK OF CHANNELS TO FACILITATE WATER FLOW IN RAIN SHOWER CONDITIONS AND/OR TO FACILITATE POWER & COMMUNICATION WIRING.

WARRANTY

5 YEAR WARRANTY AGAINST MANUFACTURER'S DEFECTS UNDER NORMAL USE CONDITIONS.

Made In Canada

To order visit [IRON COMPANY](#)