



THE  
**LOGICAL**  
**OPTION**  
WHEN IT COMES TO  
GYM FLOORING.

**GYMlogix GYM FLOORING SPECIFICATIONS**

**PRODUCT STANDARDS AND RESULTS**

| Item                    | Standard     | Rating for Rolls and Tiles           |
|-------------------------|--------------|--------------------------------------|
| Tensile Strength        | ASTM D412    | 266 PSI                              |
| Density                 | ASTM D3676   | 69.2lbs./cubic foot                  |
| Tear Resistance         | ASTM D413    | Average Elongation at break 1.55     |
| Hardness                | ASTM D2240   | Shore A 65 +/-5                      |
| Compression Set         | ASTM D395    | -4.90%                               |
| VOC Emissions           | ASTM DS116   | 0.5 mg/m2 or less                    |
| Flammability            | ASTM D2859   | PASS                                 |
| Resistance to Chemicals | F-925-02     | Resistant to most acids and chlorine |
| Coefficient to Friction | ASTM D1894/5 | >0.8                                 |

**GYM FLOORING DIMENSIONS-ROLLS**

|                   |                       |           |
|-------------------|-----------------------|-----------|
| <b>Width:</b>     | Standard — 4'         |           |
| <b>Thickness:</b> | Standard — 3mm - 12mm |           |
| <b>Length:</b>    | Standard — 25' & 50'  |           |
| <b>Weight:</b>    | Thickness             | Per sq ft |
|                   | 6mm (1/4")            | 1.25 lb   |
|                   | 8mm (5/16")           | 1.65 lb   |
|                   | 9mm (3/8")            | 2 lb      |
|                   | 12mm (1/2")           | 2.5 lb    |
|                   | 19mm (3/4")           | 4 lb      |
|                   | <i>Tiles only</i>     |           |



*Premium gym flooring available in rolls, tiles or mats. Can be interlocking or straight cut. Available in black, 10% color. Additional color percentage requires special ordering.*

